

BASE Polyurethane	TECHNICAL DATA SHEET TWO PART, SOLVENT FREE, GENERAL PURPOSE ADHESIVE	PRODUCT Intastop Anti Pic Sealant
SOLIDS 100%	<p><u>DESCRIPTION</u></p> <p>Intastop Anti Pic Sealant is a two-part adhesive consisting of an off-white coloured Paste base and a dark brown liquid curing agent</p> <p>When mixed Intastop Anti Pic Sealant has a paste like consistency with gap filling capability and cures to form a hard, tough, resilient bond which is resistant to water, solvents and heat.</p> <p>Intastop Anti Pic Sealant can be used for bonding a wide range of materials including metals, wood and plastics and is frequently used in the Building Industry for laminating plastic fascia's to board or concrete. Intastop Anti Pic Sealant is also for bonding pedestals onto floors for raised applications.</p> <p><u>APPLICATION</u></p> <p>Ensure that both surfaces are clean, dry and free from dust. Mix 11 parts of base (A) with 1 part of curing agent (B), by weight and stir thoroughly. Once mixed the adhesive has a pot life of approximately 75 minutes @ 20°C and has cured sufficiently for most purposes in 6 hours @ 20°C.</p> <p>Apply the adhesive to one substrate only by means of a knife, notched trowel, spatula etc. The two substrates should be brought together as quickly as possible and held under pressure until the adhesive has sufficiently cured to permit handling of the laminate.</p> <p>Full cure is not achieved for 24 hours or more depending on the ambient temperatures.</p> <p><u>HANDLING AND STORAGE</u></p> <p>Part A. Store in a dry place between 5°C and 30°C.</p> <p>Part B. Store in a dry place between 10°C and 30°C. Avoid contamination with moisture</p> <p style="text-align: right;">CONTINUED OVER PAGE</p>	
VISCOSITY (A):Thick Paste (B):Liquid		
COLOUR (A):Off White (B):Brown		
TACK LIFE N/A		
COVERAGE 4m ² /ltr @ 0.25mm		
CLEANER Solvent 3 (whilst uncured)		
FLASH POINT See MSDS		
SHELF LIFE 3 Months@ 4°C - 25°C		



Intastop Ltd
Holly Street, Kelham St Ind Estate
Doncaster, DN1 3TR

T: 01302 364666 F: 01302 364777
E: adhesives@intastop.com
W: www.intastop.com

CONTINUATION

WARNING

Contamination with moisture will degrade Intastop Anti Pic Sealant and could generate pressure in sealed containers.

HEALTH AND SAFETY

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The hazard labels (complying with CHIP and CDG/CPL Regs).
2. Intastop Anti Pic Sealant Material Safety Data Sheet

IMPORTANT NOTICE

This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. All recommendations and suggestions are therefore made without guarantee. Samples will be provided on request to enable customers to satisfy themselves as to the suitability of the product for any specific purpose and to assess the product under their own working conditions.

Please note that the BSI/UKAS logo for BS EN ISO 9001:2000 Certification of this document refers to the Quality Management System used throughout the production of products.